

# Injection pump HTP 21000 BI-MIX 18lt

HTP 21000 BICOMPONENT is an airless hydraulic piston pump ideal for bi-component products with mixing 50:50.

It is the ideal equipment for injecting specific products for strengthening in the buildings renovation. The easy adjustment of the pressure allows to inject from low to high pressure (up to 120 Bar) without problems.

HTP 21000 BICOMPONENT in the version with 18 ltr/min delivery, besides injection, it is ideal for spraying bi-component products (mixing 50:50) ideal for injecting bi-component products for the water-barrage in the tunnel.

## Construction specifications

The electric motor is H class, that means: maximum quality and safety. It can work in very bad conditions and with very high temperature. An automatic system stops the pump when exceeding the electric safety limits. All parts in contact with the product are in stainless steel in order to grand the highest performance. HTP 21000 has been designed for an easy maintenance.

## The airless system

1. The Airless system allows a faster atomization and reduces the overspray, therefore a paint and solvent saving.
2. Less overspray means also less pollution with benefits for the worker's health.

## Destination's field

- Building
- Injection
- Chemical barrel

## Applications

- Paints
- Bicomponent for injection or covering
- Suggested guns
- Injector

## Tehnickal specifications

- Motor: Electric, singlephase
- Power: 3 HP
- Voltage 230 Volt /50 Hz
- Max. Delivery: 18 lt./min
- Ratio: 1:1
- Max Pressure: 120 Bar
- Weight: 120 Kg

## Injection pump HTP 21000 BI-MIX 18lt

<http://mscgroup.ro/en/uncategorized/injection-pump-htp-21000-bi-mix-18/>

---



Bucuresti ROMANIA

Tel: 0749074907 +40724044499

Fax: +40318105628

web: [www.msc.ro](http://www.msc.ro)

e-mail: [office@msc.ro](mailto:office@msc.ro)